

Eclipse

Pendant

Sarkıt



01115

Design luminaire Eclipse made of painted sheet steel housing with 90° adjustable inner-circle to direct light.

RAL 9005 black electrostatic paint applied. Other colors optional.


Opal diffuser enables homogeneous light output. High efficiency LED driver secures low energy loss.

Usage of halogen-free cable ensures extra safety.

LED module with 50.000h life time and CRI≥80 used.

Suitable for pendant mounting applications.

DALI dimming options available.



ECLIPSE; DKP sac gövdeli ve opal difüzörlü zarif bir sarkıt armatürüdür. 90° Yönlendirilebilir çemberi ile farklı açılarda istenilen aydınlatma sağlanabilir.

Siyah (RAL 9005) elektrostatik toz boyalıdır. Farklı renk seçenekleri mevcuttur.

Opal difüzör, UV-korunmalı akrilik (PMMA) materyalden olup, yüksek verimlilikte homojen ışık dağılımı sağlar.

Düşük kayıplı, yüksek verimli LED sürücü; halogen-free kablo; 50.000 saat ömürlü, CRI≥80 renksel geri verime sahip LED modül kullanılır.

DALI uygulama opsiyonları vardır.

Design by Omlet İstanbul Design Office



850°C	Ra ≥ 80	220-240V 50/60Hz	IP 40	LED		TS 8698 EN 60598-2-1
-------	---------	---------------------	----------	-----	--	-------------------------

Code Kod	Power Güç (W)	Light Source Işık Kaynağı	Luminous Flux Işık Akısı (lm)	Color Temp. Renk Sıcaklığı (K)	Dimensions Boyutlar (mm)	
					Ø	H
01115.122	15	LED Module	1500	4000	300	60
01115.112	15	LED Module	1450	3000	300	60
01115.402	55	LED Module	5400	4000	600	60
01115.392	55	LED Module	5300	3000	600	60
01115.163	100	LED Module	9500	4000	900	60
01115.153	100	LED Module	9400	3000	900	60