

LED Outdoor Wall Luminaire

LED Harici Aplik



06159

Housing made of RAL9016 white painted sheet steel, different colors available

UV-stabilised opal acrylic (PMMA) diffuser provides homogeneous light output



High efficiency LED driver secures low energy loss.

Usage of halogen-free cable ensures extra safety.

LED module with 50.000h life time and CRI≥80 used.

Wall surface mounting application.

Emergency, DALI dimming options available.



Yüksek kaliteli DKP sacdan üretilen gövde, beyaz (RAL 9016) elektrostatik toz boyalıdır. Farklı renk seçenekleri mevcuttur.

Dekoratif çerçeveli UV-korumalı akrilik (PMMA) opal difüzör, yüksek verimlilikte homojen ışık dağılımı sağlar.

Düşük kayıplı, yüksek verimli LED sürücü; halogen-free kablo; 50.000 saat ömürlü, CRI≥80 renksel geri verime sahip LED modül kullanılır.

Sıvaüstü aplik olarak uygulanır.

Acil durum kiti, DALI balast uygulama opsiyonları vardır.



Code Kod	Power Güç (W)	Light Source Işık Kaynağı	Luminous Flux Işık Akısı (lm)	Dimensions Boyutlar (mm)		
				W	L	H
06159.202	20	LED Module	1800	220	220	200
06159.232	40	LED Module	3500	220	220	430
06159.282	60	LED Module	5000	220	220	850