

Orion

Indoor Lighting - Recessed Lighting



TECHNICAL INFORMATION

Housing	Electrostatic coated steel sheet
Optics	Highly transmissive opal diffuser
LED Lifetime	50.000 hours
L80B50	
Mounting System	Recessed

OPTICAL SPECIFICATIONS

Light Distribution	Symmetrical
Light Output Angle	120°
UGR Value	80
Color Bin Value	Mc Adams < 3
Color Temperature (CCT)	3000K/4000K

ELECTRICAL



Power (W)	9-31W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit
Tunable White

ASSEMBLY

Installation Type Under Plaster



Order Code	W	Lm	CCT	CRI	WxLxHxH 2 (mm)	Ceiling Cutting (mm)	Kg
02120.33.30.008	9	800	3000	Ra>80	295x295x7 3x105	275x275	2,1
02120.33.40.009	9	850	4000	Ra>80	295x295x7 3x105	275x275	2,1
02121.66.30.032	31	3200	3000	Ra>80	595x595x7 3x105	575x575	4,1
02121.66.40.033	31	3300	4000	Ra>80	595x595x7 3x105	575x575	4,1

