

Proof

Indoor Lighting - Industrial Lighting



TECHNICAL INFORMATION

Housing Impact Resistant Gray - PC Injection
Diffuser High Light Transmittance Opal - PC Injection
Locking System Metal Latch - Stainless Steel

OPTICAL SPECIFICATIONS

Optics Symmetrical
Light Output Angle 120°
UGR Value UGR ≤ 22
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL



Power (W) 25-47W
Power Factor >0.95
Light Source SMD Mid Power LED
Cabling Halogen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output Drive
Ambient Temperature -20°C / +50°C
LED Lifetime L80B50 >50.000 Hour

OPTIONAL

- DALI
- Tunable White
- CRI > 90
- Plug-in Connector
- PIR Sensor
- 1-10V DIM
- Emergency Lighting Unit
- 2700K ~ 6500K
- Class-II Protection Class
- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted
Mounting Apparatus Metal Bracket



Order Code	W	Lm	CCT	Kg	L (mm)
07101.14.30.030	25	2880	3000	1,6	1185
07101.14.40.030	25	3000	4000	1,6	1185
07101.14.30.036	32	3456	3000	1,6	1185
07101.14.40.036	32	3850	4000	1,6	1185
07101.14.30.043	40	4128	3000	1,8	1185
07101.14.40.043	40	4230	4000	1,8	1185
07101.14.30.049	47	4700	3000	1,8	1185
07101.14.40.049	47	4900	4000	1,8	1185
07101.15.40.049	28	3900	4000	2	1485

