

# Dragon

Indoor Lighting - Spot Lighting



## Colour Options



## TECHNICAL INFORMATION

<b>Housing</b>	Aluminum Injection
<b>Frame</b>	Aluminum Injection
<b>Reflector</b>	Metalized Coated Reflector
<b>Paint</b>	Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

<b>Optics</b>	Symmetrical
<b>Light Output Angle</b>	24°
<b>UGR Value</b>	UGR ≤ 19
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

## ELECTRICAL




<b>Power (W)</b>	28W-37W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	COB LED
<b>Cabling</b>	Halojen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Energy Input Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

## ASSEMBLY

<b>Installation Type</b>	Under Plaster
<b>Mounting Apparatus</b>	Steel Spring



Order Code	W	Lm	Angle	CCT	CRI	ØxH (mm)	Cut-out dimensions (mm)	Kg
05310.16.30.032	28	3050	24°	3000	Ra>80-90	Ø185x146	Ø170	1,3
05310.16.40.034	28	3230	24°	4000	Ra>80-90	Ø185x146	Ø170	1,3
05310.16.30.030	30	3250	24°	3000	Ra>80-90	Ø185x146	Ø170	1,3
05310.16.40.030	30	3450	24°	4000	Ra>80-90	Ø185x146	Ø170	1,3
05310.16.30.041	37	3750	24°	3000	Ra>80-90	Ø185x146	Ø170	1,3
05310.16.40.043	37	4000	24°	4000	Ra>80-90	Ø185x146	Ø170	1,3

