

Rolling

Indoor Lighting - Recessed Lighting



TECHNICAL INFORMATION

Housing	Aluminum profile with electrostatic coating
Diffuser	Highly transmissive opal diffuser
LED Lifetime	50.000 hours
L80B50	
Mounting System	Recessed

OPTICAL SPECIFICATIONS

Light Distribution	Directional
UGR Value	80
Effectiveness Factor	106 Lm/W
Color Bin Value	Mc Adams < 3
Color Temperature (CCT)	3000K/4000K

ELECTRICAL



Power (W)	23-41W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit
Tunable White

ASSEMBLY

Installation Type Under Plaster



Order Code	W	Lm	CCT	CRI	ØxH (mm)	Cut-out dimensions (mm)	Kg
03170.38.30.023	23	2075	3000	Ra>80	380x82	370	4,6
03170.38.40.024	23	2185	4000	Ra>80	380x82	370	4,6
03170.60.30.042	41	3700	3000	Ra>80	600x82	590	7,2
03170.60.40.043	41	3900	4000	Ra>80	600x82	590	7,2

