

Tetrad-085

Indoor Lighting - Spot Lighting



Colour Options



Ral 9016



Ral 9006



Ral 9005

TECHNICAL INFORMATION

Housing	Metal sheet
Diffuser	Opal with High Light Transmittance
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	110°
UGR Value	UGR ≤ 22
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL






Power (W)	4-19W
Power Factor	>0.95
Light Source	SMD Mid Power LED
Cabling	Halojen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	Yüksek Verimli Sabit Akım Çıkışlı
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Emergency Lighting Unit	- CRI > 90
- 2700K ~ 6500K	- Different RAL Color Options
- Plug-in Energy Input Connector	- Class-II Protection Class
- PIR Sensor	- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Metal Suspended Ceiling



Order Code	W	Lm	Angle	CCT	CRI	WxLxH (mm)	Kg
05348.11.30.001	3,5	100	110°	3000	Ra>80	101x101	0,2
05348.11.40.001	3,5	200	110°	4000	Ra>80	101x101	0,2
05348.12.30.004	7	400	110°	3000	Ra>80	101x201	0,4
05348.12.40.005	7	500	110°	4000	Ra>80	101x201	0,4
05348.22.30.009	14	900	110°	3000	Ra>80	202x202	0,9
05348.22.40.012	14	1000	110°	4000	Ra>80	202x202	0,9

