

Modus-DC

Indoor Lighting - Spot Lighting



TECHNICAL INFORMATION



Housing
Reflector
Light Source
Driver
Input
Voltage/Input
Factor
Working
Temperature

OPTICAL SPECIFICATIONS

ELECTRICAL

OPTIONAL

ASSEMBLY



Order Code	W	Lm	Angle	CCT	CRI	L (mm)	Kg
05638.97.30.027	30	3330	12°	3000	Ra>80	170	1,2
05638.97.40.028	30	3510	12°	4000	Ra>80	170	1,2
05638.97.30.028	30	3330	24°	3000	Ra>80	170	1,2
05638.97.40.029	30	3510	24°	4000	Ra>80	170	1,2
05638.97.30.029	30	3330	36°	3000	Ra>80	170	1,2
05638.97.40.030	30	3510	36°	4000	Ra>80	170	1,2
05638.97.30.016	20	2110	12°	3000	Ra>80	150	1,2
05638.97.40.017	20	2220	12°	4000	Ra>80	150	1,2
05638.97.30.017	20	2110	24°	3000	Ra>80	150	1,2
05638.97.40.018	20	2220	24°	4000	Ra>80	150	1,2
05638.97.30.018	20	2110	36°	3000	Ra>80	150	1,2
05638.97.40.019	20	2220	36°	4000	Ra>80	150	1,2

