



Sparrow

Indoor Lighting - Spot Lighting



Colour Options



Ral 9016



Ral 9006



Ral 9005

TECHNICAL INFORMATION

Housing	Aluminum Injection
Frame	Aluminum Injection
Reflector	Metallized Surface Optics
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	36°-24°-10°
UGR Value	UGR ≤ 22
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL



Power (W)	15-20W
Power Factor	>0.95
Light Source	COB LED
Cabling	Halojen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- Tunable White
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	

ASSEMBLY

Installation Type Ray Socket



Order Code	W	Lm	Angle	CCT	CRI	ØxL (mm)	Kg
05668.80.30.017	15	1660	36°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.018	15	1720	36°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.021	20	2170	36°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.022	20	2270	36°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.014	15	1640	24°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.015	15	1750	24°	4000	Ra>80	Ø60x163x90	1,2
05668.80.30.018	20	1850	24°	3000	Ra>80	Ø60x163x90	1,2
05668.80.40.019	20	1950	24°	4000	Ra>80	Ø60x163x90	1,2



Verilen tüm elektriksel değerler nominal değerlerdir. Işık akısı ve bağlı elektrik yükü +/- %10 luk bir başlangıç toleransına tabidir. Renk sıcaklığı toleransı: +/-150 K. Katalogta ve web sitesinde yer alan teknik parametreler ve ürün kodlarını içeren bilgiler, projelere göre yapılan kişiselleştirmelerden dolayı standart ürünlerden farklılık gösterebilir. İkizler Aydınlatma, ürünlerde haber vermeden değişiklik yapma hakkına sahiptir.

