



Draw IP65

Indoor Lighting - Industrial Lighting



TECHNICAL INFORMATION

Housing	Highly transmissive PC opal diffuser
Optics	
LED Lifetime	50.000 hours
L80B50	
Mounting System	Surface

OPTICAL SPECIFICATIONS

Light Distribution	Symmetrical
Light Output Angle	120°
UGR Value	80
Color Bin Value	Mc Adams < 3
Color Temperature (CCT)	4000K

ELECTRICAL

Power (W)	26-48W
Power Factor	>95
Light Source	SMD Mid Power LED
Cabling	Halojen-Free
Input Voltage	220-240V / 50-60 Hz

OPTIONAL

DALI
Emergency Lighting Unit

ASSEMBLY

Order Code	W	Lm	CCT	CRI	WxLxH (mm)
07102.67.40.030	26	3000	4000	Ra>80	73x1165x79
07102.67.40.041	37	4160	4000	Ra>80	73x1165x79
07102.67.40.049	46	4930	4000	Ra>80	73x1165x79
07102.67.40.038	32	3800	4000	Ra>80	73x1445x79
07102.67.40.045	40	4800	4000	Ra>80	73x1445x79
07102.67.40.052	48	5200	4000	Ra>80	73x1445x79

