



Anemon-1250

Outdoor Lighting - Facade Lighting



Order Code	W	Lm	CCT	CRI	WxLxH (mm)	Kg
05255.12.30.060	55	6050	3000	Ra>80	58x1250x70	5,6

TECHNICAL INFORMATION

Housing	Extruded Aluminum Profile
Frame	Matte Anodized Finish
Glass	Tempered Clear Glass
Reflector	Acrylic Optical Lens
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Light Distribution	Symmetrical
Light Output Angle	10°-25°-45°-120°
UGR Value	UGR ≤ 25
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL

Power (W)	55W
Power Factor	>0.95
Light Source	High Power LED
Cabling	Halogen-Free
Input Voltage	220-240V / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Hour

OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- 2700K ~ 6500K	- CRI > 90
- Different RAL Color Options	- Plug-in Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

ASSEMBLY

Installation Type Surface Mounted

