

# Mino 080

Indoor Lighting - Spot Lighting



Colour Options



## TECHNICAL INFORMATION

<b>Housing</b>	Aluminum Injection
<b>Frame</b>	Aluminum Injection
<b>Reflector</b>	Metallized Surface Optical Reflector + Glass
<b>Paint</b>	Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

<b>Optics</b>	Symmetrical
<b>Light Output Angle</b>	32°
<b>UGR Value</b>	UGR ≤ 16
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

## ELECTRICAL



<b>Power (W)</b>	7-10W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	COB LED
<b>Cabling</b>	Halojen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	Yüksek Verimli Sabit Akım Çıkışlı
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

- DALI	- 1-10V DIM
- Tunable White	- Emergency Lighting Unit
- CRI > 90	- 2700K ~ 6500K
- Different RAL Color Options	- Plug-in Energy Input Connector
- Class-I Protection Class	- AC-DC Supply(MBS)

## ASSEMBLY

**Installation Type** Under Plaster



Order Code	W	Lm	Angle	CCT	CRI	ØxH (mm)	Cut-out dimensions (mm)	Kg
05112.08.40.010	10	1050	32°	4000	Ra>80	Ø82x84	Ø75	0,2

