

# Target - Wallwasher

Indoor Lighting - Spot Lighting



Colour Options



## TECHNICAL INFORMATION

**Housing** Aluminum Injection  
**Reflector** PC Optical Reflector  
**Paint** Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

**Optics** Asymmetrical  
**Light Output Angle** 83°  
**UGR Value** UGR ≤ 22  
**CRI** CRI ≥ 80  
**Color Bin Value** Mc Adams ≤ 3

## ELECTRICAL




**Power (W)** 9W  
**Power Factor** >0.95  
**Light Source** High Power LED  
**Cabling** Halojen-Free  
**Input Voltage** 220-240V AC / 50-60 Hz  
**LED Driver** High Efficiency Constant Current Output  
**Ambient Temperature** -20°C / +50°C  
**LED Lifetime L80B50** >50.000 Hour

## OPTIONAL

- DALI
- Tunable White
- CRI > 90
- Different RAL Color Options
- Class-I Protection Class
- 1-10V DIM
- Emergency Lighting Kit
- 2700K ~ 6500K
- Plug-in Energy Input Connector
- AC-DC Supply(MBS)

## ASSEMBLY

**Installation Type** Under Plaster  
**Mounting Apparatus** Steel Spring



| Order Code      | W | Lm  | Angle | CCT  | CRI   | WxLxH (mm) | Cut-out dimensions (mm) |
|-----------------|---|-----|-------|------|-------|------------|-------------------------|
| 05115.88.30.018 | 9 | 540 | 83°   | 3000 | Ra>80 | 155x50x51  | 145x40                  |

