

RAL 9005 RAL 9006


SKATE-R


01183

Acoustic Comfort and Low Glare Lighting

Skate-R is a hybrid solution that combines sound-absorbing acoustic felt panels with high-efficiency LED lighting in a single product. Thanks to its glare-controlled reflector and lens optics, it offers visual comfort with a UGR≤16, while the acoustic felt panel reduces echo, improving sound quality in working environments.

It adapts to architecture with different felt colors and customizable panel sizes. It provides both acoustic treatment and high-quality lighting solutions in a single product for open offices, meeting rooms, training areas, and social living spaces.





General Information	
Housing	Aluminum Extruded
Panel	Acoustic Felt
Optics	Optical Reflector
Paint	Electrostatic Powder Paint
Insulation Class	Class I
Product Dimensions [mm]	295(W)x1640(L)x80(H)
Mounting Type	Pendant
Mounting Part	Height Adjustable Steel Wire

Electrical Info	
Power	30W
Power Factor	>0.95
Light Source	SMD Mid Power LED
Cabling	Halogen-Free
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	Constant Current
Ambient Temperature	-20°C / +50°C
LED Lifetime L70	>102.000 Hour

Lighting Technology	
Light Output Angle	80°
UGR Value	UGR ≤ 16
CRI [Ra]	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

Optional
DALI / 1-10V
CRI>90 , 2700K~6500K , Tunable White
Emergency Lighting Unit

Order Code	W	Lm	CCT	WxLxH (mm)	Kg
01183.21.30.035.N000.S	30	3500	3000	295x1640x80	4,50
01183.21.40.036.N000.S	30	3600	4000	295x1640x80	4,50

Verilen tüm elektriksel değerler nominal değerlerdir. Işık akısı ve bağlı elektrik yükü +/- %10 luk bir başlangıç toleransına tabidir. Renk sıcaklığı toleransı: +/-150 K.
Katalogda ve web sitesinde yer alan teknik parametreler ve ürün kodlarını içeren bilgiler, projelere göre yapılan kişiselleştirmelerden dolayı standart ürünlerden farklılık gösterebilir.
İkizler Aydınlatma, ürünlerde haber vermeden değişiklik yapma hakkına sahiptir.

+90 (216) 397 22 16
info@ikizleraydinlatma.com