

Tiny-T

Indoor Lighting - Spot Lighting, Trimless
Spot Lighting



Colour Options



Ral 9016

TECHNICAL INFORMATION

Housing	Aluminum Injection
Frame	Aluminum Injection-Trimless
Reflector	Metal-White Painted
Diffuser	Clear Lens
Paint	Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics	Symmetrical
Light Output Angle	37°
UGR Value	UGR ≤ 19
CRI	CRI ≥ 80
Color Bin Value	Mc Adams ≤ 3

ELECTRICAL




Power (W)	10W
Light Source	Halojen-Free
Cabling	220-240V AC / 50-60 Hz
Input Voltage	220-240V AC / 50-60 Hz
LED Driver	High Efficiency Constant Current Output
Ambient Temperature	-20°C / +50°C
LED Lifetime L80B50	>50.000 Saat

OPTIONAL

2700K ~ 6500K
Lens Angle - 24°/ 28°
Plug-in Energy Input Connector

ASSEMBLY

Installation Type	Under Plaster
Mounting	Trimless Frame
Apparatus	



Order Code	W	Lm	Angle	CCT	ØDx(H)	Cut-out dimensions (mm)	Kg
05212.04.04.007	10	840	37°	4000	Ø46x105mm	Ø45mm	0,185

