

Tiny-T

Indoor Lighting - Spot Lighting, Trimless
Spot Lighting



Colour Options 
Ral 9016

TECHNICAL INFORMATION

Housing Aluminum Injection
Frame Aluminum Injection-Trimless
Reflector Metal-White Painted
Diffuser Clear Lens
Paint Electrostatic Powder Paint

OPTICAL SPECIFICATIONS

Optics Symmetrical
Light Output Angle 36°
UGR Value UGR ≤ 19
CRI CRI ≥ 80
Color Bin Value Mc Adams ≤ 3

ELECTRICAL




Power (W) 10W
Light Source COB LED
Cabling Halojen-Free
Input Voltage 220-240V AC / 50-60 Hz
LED Driver High Efficiency Constant Current Output
Ambient Temperature -20°C / +50°C
LED Lifetime L80B50 >50.000 Saat

OPTIONAL

2700K ~ 6500K
Lens Angle - 24°/ 28°
Plug-in Energy Input Connector

ASSEMBLY

Installation Type Under Plaster
Mounting Trimless Frame
Apparatus



Order Code	W	Lm	Angle	CCT	ØDx(H)	Cut-out dimensions (mm)	Kg
05212.04.30.007	10	740	36°	3000	Ø46x105mm	Ø45mm	0,185

