

# Deep-Y

Indoor Lighting - Spot Lighting, Surface Mounted Lighting



## TECHNICAL INFORMATION

<b>Housing</b>	Extruded Aluminum Profile
<b>Frame</b>	Aluminum Injection
<b>Reflector</b>	Metallized Surface Optical
<b>Paint</b>	Electrostatic Powder Paint

## OPTICAL SPECIFICATIONS

<b>Optics</b>	Symmetrical
<b>Light Output Angle</b>	36°
<b>UGR Value</b>	UGR ≤ 19
<b>CRI</b>	CRI ≥ 80
<b>Color Bin Value</b>	Mc Adams ≤ 3

## ELECTRICAL



<b>Power (W)</b>	10W
<b>Power Factor</b>	>0.95
<b>Light Source</b>	COB LED
<b>Cabling</b>	Halojen-Free
<b>Input Voltage</b>	220-240V AC / 50-60 Hz
<b>LED Driver</b>	High Efficiency Constant Current Output
<b>Ambient Temperature</b>	-20°C / +50°C
<b>LED Lifetime L80B50</b>	>50.000 Hour

## OPTIONAL

DALI  
1-10V DIM  
Emergency Lighting Kit  
CRI > 90  
2700K ~ 6500K  
Different RAL Color Options

## ASSEMBLY

<b>Installation Type</b>	Surface Mounted
<b>Mounting</b>	Screw Dowel Set
<b>Apparatus</b>	



Order Code	W	Lm	Angle	CCT	CRI	ØxH (mm)	Kg
09111.90.30.009	10	700	36°	3000	Ra>80	80x100	0,4

