


# Sinus

Indoor Lighting - Cove Lighting



Colour Options



Ral 9006

## TECHNICAL INFORMATION

**Housing** Anodized aluminum profile  
**Diffuser** Extrusion Diffuser  
**Paint** Anodized Coating

## OPTICAL SPECIFICATIONS

**Optics** Symmetrical  
**Light Output Angle** 120°  
**UGR Value** UGR ≤ 22  
**CRI** CRI ≥ 80  
**Color Bin Value** Mc Adams ≤ 3

## ELECTRICAL

**Power (W)** 1.4-21W  
**Power Factor** >0.95  
**Light Source** SMD Mid Power LED  
**Cabling** Halogen-Free  
**Input Voltage** 220-240V AC / 50-60 Hz  
**LED Driver** High Efficiency Constant Voltage Output  
**Ambient Temperature** -20°C / +50°C  
**LED Lifetime L80B50** >50.000 Hour



## OPTIONAL

- DALI  
- Tunable White  
- CRI > 90  
- Different RAL Color Options  
- Class-II Protection Class

- 1-10V DIM  
- Emergency Lighting Unit  
- 2700K ~ 6500K  
- Plug-in Connector  
- AC-DC Supply(MBS)

## ASSEMBLY

**Installation Type** Surface Mounted  
**Mounting Apparatus** Metal Bracket



Order Code	W/m	Lm	CCT	CRI	WxHxL (mm)	Kg
06132.22.40.022	21	2260	4000	Ra>80	21x18x1515	0,38

